

Options for stainless steel diaphragm pressure gauges

DG: H

Process connection			
Groove/tongue as per EN 1092-1			Option
Connection G $\frac{1}{4}$ B (channel hole \varnothing 6 mm)			Option
Connection $\frac{1}{4}$ NPT (channel hole \varnothing 6 mm)			Option
Connection $\frac{1}{2}$ NPT (channel hole \varnothing 10 mm)			Option
Connection M20 x 1.5 (channel hole \varnothing 10 mm)			Option
Other connection threads			On request
Channel hole \varnothing 10 mm with connection G $\frac{1}{2}$ B			Standard
VARIVENT®/VARINLINE®	Type N (D = 68 mm)	PN 25	On request
Neumo BioControl	D65 and D80	PN 25	On request
Flush mounted connection flange			
As per EN 1092-1/B1 (extra charge over and above connection G $\frac{1}{2}$ B)	Nominal diameter	Nominal pressure	
	DN 25 (0/1 bar to 0/6 bar)	PN 40	Option
	DN 50	PN 40	Option
	DN 80	PN 40	Option
Other connection flanges			On request
Glycerine filling (\geq 1 bar)			
Nominal size 100			Option
Nominal size 160			Option
Other			
Vacuum proof (\geq 0/4 bar)			Standard
Electrical contacts (\geq 0/0.6 bar)			See page 471