

## Probe for ÖWWG 3 year of manufacture 09/2013 and later



### Application

For the detection of liquids with a flash point of >55 °C. Suitable for the following media: water, fuel oil, diesel fuel or low-viscosity lubricating oils, motor oils, hydraulic oils, vegetable oils and transformer oils, antifreeze agents, oil-water mixtures and emulsions.

### Versions

|   | Part no. |
|---|----------|
| Probe for ÖWWG 3 year of manufacture 09/2013 and later Cable length 3.2 m | 44516    |
| Probe for ÖWWG 3 year of manufacture 09/2013 and later Cable length 10 m  | 44484    |
| Probe for ÖWWG 3 year of manufacture 09/2013 and later Cable length 25 m  | 44482    |
| Probe for ÖWWG 3 up to year of manufacture 08/2013 Cable length 3.2 m     | 44481    |
| Probe fuse  | 44495    |
| Mains fuse  | 10820    |
| EnOcean® wireless module TCM 320  | 78082    |

Blue part no. = in-stock items

### Description

Suitable for ÖWWG 3. The probe is mounted at the lowest point of the object to be monitored or in the drip pan. The alarm is triggered by the alarm unit when the probe comes into contact with liquid.



## Technical specifications

**Probe diameter**  
14 mm

**Response level**  
17 mm

**Cable length**  
3.2 m, 10 m or 25 m